

PVC COATED GALVANIZED RIGID METAL CONDUIT

(ANSI C80.1 UL 6 WWC581)

RAC Dimensions and Weights Chart
 (Standard:UL6A ANSI C80.1 WW-C-540C)

CATALOG NUMBER	SIZE	OD mm(in)	OD WITH PVC mm(in)	THICKNESS mm(in)	FINISHED THICKNESS* mm(in)	LENGHT m(ft)	U-WEIGHT kg/pcs (pound/pcs)	PACKING pcs/bundle
005.030.050	1/2	21.3	23.3	2.64	3.71	3.03	3.67	127
005.030.075	3/4	26.7	28.7	2.72	3.79	3.03	4.88	91
005.030.100	1	33.4	35.4	3.20	4.27	3.02	7.19	61
005.030.125	1 1/4	42.2	44.2	3.38	4.45	3.02	9.78	37
005.030.150	1 1/2	48.3	50.3	3.51	4.58	3.02	11.72	37
005.030.200	2	60.3	62.3	3.71	4.78	3.02	15.64	37
005.030.250	2 1/2	73.0	75.0	4.90	5.97	3.01	24.77	19
005.030.300	3	88.9	90.9	5.21	6.28	3.01	32.36	19
005.030.350	3 1/2	101.6	103.6	5.51	6.58	3.00	39.18	10
005.030.400	4	114.3	116.3	5.72	6.79	3.00	45.96	10
005.030.500	5	141.3	143.3	6.20	7.27	3.00	61.98	7
005.030.600	6	168.3	170.3	6.76	7.83	3.00	80.79	7

Notes: Norm ANSI C80.1/UL 6)

*:Thickness with PVC&PU coated
 Couplings are packaged separately

PVC COATED RIGID COUPLING



CATALOG NUMBER	Size	Lengths mm(in)	U-WEIGHT kg/pcs(pound/pcs)	PACKING Pcs/bundle
015.020.050	1/2	95.3	0.058	200
015.020.075	3/4	95.3	0.085	120
015.020.100	1	139.7	0.148	50
015.020.125	1 1/4	139.7	0.193	35
015.020.150	1 1/2	146.1	0.252	25
015.020.200	2	150.8	0.346	20
015.020.250	2 1/2	174.7	0.832	16
015.020.300	3	178.6	1.215	12
015.020.350	3 1/2	180.2	1.701	10
015.020.400	4	182.6	1.386	10
015.020.500	5	187.3	2.250	5
015.020.600	6	188.9	3.600	5